SPECIFICATIONS

ODEL NO.	TA850	TA1100
ATEO POWER	2X300W RMS / 8 OHMS 2X550W RMS / 4 OHMS MONO BRIDGE 1000W RMS/8 OHMS MONO PARALLEL 1000W RMS/ 2OHMS	2X400W RMS / 8 OHMS 2X700W RMS / 4 OHMS MONO BRIDGE 1200W RMS / 8 OHMS MONO PARALLEL 1200W RMS / 2 OH
OTAL HARMONIC STORTION	<0.05%	<0.05%
REQUENCY RESPONSE	10Hz-20KHz+0, -1.5dB	10Hz-20KHz+0, -1.5dB
AMPING FACTOR	>200.8 OHMS	>200.8 OHMS
LEW RATE	>30V/us	>30V/us
N RATIO	>105dB	>105dB
PUT SENSITIVITY IMPEDANCE	+3dB(1.4V) 20K OHMS	+3dB(1.4V) 20K OHMS
ED INDICATION	CLIP/BRIDGE/PROTECT	CLIP/BRIDGE/PROTECT
MENSIONS	482X132X445	482X132X445
ONTINUOUS	20Hz To 20KHz,	20Hz To 20KHz,
ONE WAVE	220/110 V.A.C.	220/110 V.A.C.
EIGHT	22Kg	26Kg
MENSION	483x315x88mm	483x315x88mm